

HYDRONYLON® liquid roof membranes

Product data sheet
Release 1/2017

PRIMING EMULSION

(EG)

(Mineral roof surfaces)

1. Product description and application.

PRIMING EMULSION (EG) is a ready-to-use, fine particle, deep-penetrating primer based on high-quality acrylic resins. It is designed for priming and strengthening of absorbent, over absorbent or weakened mineral roofing substrate, e.g. concrete, screeds (cement, anhydrite, gypsum screeds), gypsum boards, any types of plaster (cement, gypsum plaster etc.) or wall materials, i.e. brick, ceramic, silicate or aerated concrete masonry.

2. Application instructions:

2.1. Preparing the product

PRIMING EMULSION (EG) is ready for direct use. It must not be mixed with other chemicals or thickened. It may be diluted with clean water by keeping proportions of 1 part of emulsion per

2.2. Preparing roof surfaces:

All roof surfaces should be dry and clean. Any grease, dust, dirt or loose parts should be removed.

2.3. Application:

For best effects use without diluting. Apply single, thin coat with a paint roller or brush.

For absorbent or badly damaged surfaces apply 2 coats. For the first coat use emulsion diluted with clean water (please ensure 1:1 proportions when diluting). For the second coat use undiluted emulsion. Ensure that the first coat is completely dry before applying second coat. We recommend a curing period of min 12 hours between coats.

after applying the last coat of emulsion.

Ambient and ground temperature should be between +5°C to +35°C during the application process.

After use tools should be washed with clean water with clean water.

Usage:

Recommended application: 0.2 kg/m²

3. Storage and transport.

Containers should be kept tightly sealed, in a temperature between +5°C and +30°C, in a way that prevents them from being damaged or smashed.

4. Comments

General Health and Safety rules must be followed.
S2 - keep away from children.

The manufacturer guarantees quality of the product but not the way it is used. All recommendations provided in the product data sheet should be followed. The above information doesn't replace contractor training and does not exempt the contractor from following Health and Safety rules or Building Regulations.

Please don't hesitate to contact the manufacturer directly on + 48 (32) 700-92-85 if you require additional information.

Packaging: 5 kg

Shelf life:

12 months - in sealed, original packaging.

The product contains 1,2-benzisothiazol-3-one; post-reaction mixture of 5-chloro-2-methyl-2h-isothiazol-3-one [EC number 247-500-7] and 2-methyl-2H-isothiazol-3-on [EC number 220-239-6] (3:1). The product may cause allergic reaction.

Marketing Authorisation Holder:

Proof-Tech Sp. z o.o.
42-677 Szalsza ul.
Tarnogórska 9